

**NEW**

**DIGITAL THERMOMETER  
DT301 / DT302 / DT304**

**NEW**

**DT301 / DT302 / DT304**

The DT301 / DT302 / DT304 digital thermometers accept type J, K, T or E probes to accommodate your existing process technology. Its backlight displays are easy to read, even in low-light areas. The DT302 allows you to measure two inputs simultaneously. The DT304 allows you to measure four inputs simultaneously.

- Accepts K, J, T, or E thermocouples
- Time-stamped multifunction record
- Relative function displays temperature change
- Differential temperature (DT302 / DT304)
- Temperature in °C or °F
- Large, backlit display
- Latest technology



**SPECIFICATIONS**

Power Supply	2x AAA Alkaline 1.5V battery
Probes	Type K, J, T or E thermocouple
Range	
Type K	-328 to 2498°F (-200 to 1370°C)
Type J	-346 to 2192°F (-200 to 1200°C)
Type T	-418 to 752°F (-250 to 400°C)
Type E	-238 to 1832°F (-150 to 1000°C)
Accuracy	+/- 0.1% reading + 1.0°F (+0.5°C)
Resolution	0.1°F, 1°F (0.1°C, 1°C)

**ACCESSORIES**

Standard bead probes
Air probes
Surface probes
Liquid probes
Right angle probes
Soft carrying case
Hard carrying case

**INPUT OPTIONS**

Model	Inputs
DT301	One
DT302	Two
DT304	Four

**STANDARD**

2x AAA battery
Standard bead probe, Type J