

Analytical Industries Inc.

2855 Metropolitan Place, Pomona, CA 91767 USA ♦ Tel: 909-392-6900, Fax: 909-392-6900, e-mail: sales-medical@aii1.com,Website: www.aii1.com

Oxygen Sensor Model	PSR-11-917-J7	
Measuring Range	0-100% O2	
Signal Output (1)	7-13 mV	[_ [28.45] _
Response Time 90%	13 Seconds	Ø1.120
Accuracy Full Scale (2)	<u>+</u> 1%	
Accuracy FS Over Operating Range (3)	<u>+</u> 5%	
Drift % Signal Month (2)	< 1%	(15.24) Ø.600
Linearity (2)	<u>+</u> 1%	[44.70] 1.760 [40.77]
Humidity Non-Condensing	0-99% RH	[26.16] 1.605 \$\phi\$ 1.030
Temperature Coefficient	Compensated	M16 X 1 THREADS [6.73]
Operating Temperature	0-45° C	.265 NOTE: NOTE: FOR OPTIMUM PERFORMANCE THIS END FACING DOWN OT HORIZONTAL
Operating Pressure	Constant 5-30 PSIG	[38.36]
Flow Rate	.1-10 LPM	1.440 [27.33] 1.076 [11.80] 4.465
Expected Life (1)	60 Months	[14.61] \$\phi\$.575
Storage (4)	0 to 40°C	[20.70] Ø .815
Warranty (5)	18 Months	
Electrical Connections	Female Phono Jack	
Packaging	Polyetylene bag in 3" x 3" x 1.5" paper box	
Recommended Storage	< 6 months	

- (1) In air @ 25° C and 1 atm. Expected life varies inversely with changes in O2 concentration, temperature, pressure.
- $(2) \ Under \ constant \ conditions. \ Calibrate \ as \ near \ sample \ conditions \ as \ possible. \ Calibrate \ with \ 95-100\% \ oxygen \ for \ measurements \ > 40\% \ oxygen.$
- (3) Once the signal output stabilizes following a step change in temperature.
- (4) Recommended 0-40° C. Sensors may be stored at -10 to 55° C on an intermittent basis only.
- (5) Ex-factory unless agreed to in writing. Under normal application conditions sensor is warranted to be free of defects in material and workmanship for the period specified above proved the sensor is properly installed and operated. Analytical Industries Inc. shall not be liable for buyer's negligence, misapplication, alteration or abuse. The sole remedy for a sensor determined to be defective by Analytical Industries Inc. is limited to replacing the defective sensor.